





The bottom suction submersible pump MINISUB is a pump designed for various applications in agricultural and residential markets. This pump, with the suction located at the bottom part, can be used for water distribution and can be installed in any type of cistern. Given the characteristics of their design and construction is suitable for handling clean water and treated effluent.

The suction at the bottom guarantees the quiet operation of the pump, motor cooling efficiency and the not required use of an external sleeve for cooling. The pumped liquid is circulated through the sleeve of the motor, ensuring optimum operating temperature and reducing the noise.

### **Performance Range**

- Flow from 2.5 GPM to 28 GPM.
- Head up to 203 ft.
- Minimum admissible ambient temperature: + 5 ° C.

#### **Features**


- Continuous duty: Pearl effluent pumps can operate continuously without damage to any component.
  Impeller floating system: designed to guarantee the best
- performance and durability for sand handling.
- Available in 115 V or 230 V.
- 8 foot power cord.
- Construction according to standards: CSA-C22.2 No. 108-14; UL 778-2014.

### DISCHARGE **TECHNOPOLYMER BEARING NYLATRON** CHECK VALVE **TECHNOPOLYMER EXTERNAL SLEEVE** STAINLESS STEEL POLISHED **IMPELLERS** ACETAL DIFFUSERS POLYCARBONATE WEAR RING **POLYCARBONATE / STAINLESS STEEL** SHAFT STAINLESS STEEL SUCTION GRID STAINLESS STEEL

### **Construction Materials**



## **Curves and Performance Data**



### Performance Data


	MODEL	HP	CAPACITY	(	)	2.	.5	Ę	5	7.	.5	1	0	12	2.5	1	5	17	<b>'</b> .5	2	0	22	2.5	2	!5	27	7.5
-	1PH / 3PH	пr	[GPM]	ft	mts	ft	mts	ft	mts	ft	mts	ft	mts														
	4MSP 05	0.5	LI ( <del>5</del> 4)	167	51	160	49	157	48	150	46	140	43	130	40	117	36	105	32	90	27	75	23	60	18		
	4MSP 07	0.7	H (ft)	194	59	190	58	185	56	175	53	165	50	157	48	145	44	137	42	117	36	101	31	83	25	64	20

# **Pump Dimensions**

MODEL	DISCHARGE		DIMENSIO	NS INCHES		LBS
1 PH / 3PH	DN	Ø	h1	h2	h3	1~
4MSP 05	1 1/4"	3 3/4	22	20	2	17.5
4MSP 07	1 1/4"	3 3/4	28	26	2	20

# Packaging Dimensions

1 PH / 3PH         lbs         inch         inch           4MSP 05         18.5         30.5         5.9         5.5	QTY.	Alt	А	L	WEIGHT	MODEL
4MSP 05         18.5         30.5         5.9         5.5	9	inch	inch	inch	lbs	1 PH / 3PH
	PCS/20	5.5	5.9	30.5	18.5	4MSP 05
4MSP 07 21 30.5 5.9 5.5	PCS/21	5.5	5.9	30.5	21	4MSP 07



MINISUB

Pearl





PD WATER SYSTEMS LLC | 2310 W. 76TH ST. HIALEAH, FL 33016 | 954-474-9090 www.pearlwatersystems.com

VERSION 04/2022